KOMBIC 100 DOWNLIGHT

LAMP
Worktitude for light

K11SQ2040WF927NBB — **KOMBIC 100 SQ 2000 IP43 9VWW WFL BK/BK**

Description:

Finish: Matte black RAL 9011

TECHNICAL SPECIFICATIONS:

Light output:	1.341 lm	**ºK :**	2700
Plum:	14W	**CRI :**	90
Efficacy:	95,8 lm/w	**R9 :**	57
UGR:	<19		
Type:	COB		
LED Lifetime:	>100.000h L90 B10 (Ta=25ºC)		
Power:	12,2W		

Light output tolerance +/- 10%

IP
20 INT
43 EXT

EPD

CUSTOM MADE OPTIONS:

1-10V | | ⬛ | ✳ | ↑lm | LED RETAIL | 🌐 | PUSH | TRIAC | K

K11SQ2040WF927NBB   KOMBIC 100 SQ 2000 IP43 9VWW WFL BK/BK

PHOTOMETRIC DATA :

K11SQ2040WF927NBB

η = 100%

Imax = 1274 cd/klm

UTE:

CIE: 98 100 100 100 100

alpha = 57,1º

BACK   FRONT

50,1 %   50,1 %

Melanopic Lux Ratio: 0.495

Rf 91.6 – Rg 99.8

LAMP reserves the right to change the technical specifications of their products. These changes will allow the continual improvement of the products and will also ensure the conformity to current legal changes. Updated information is always available in our website www.lamp.es

03-06-2025

Pág.   2 / 2

Data according to regulations 2019/2020/EU and 2019/2015/EU