


KOMBIC 100 DOWNLIGHT

K11SQ2040WF930DWW



KOMBIC 100 SQ 2000 IP43 9WW WFL DA WH/WH

Description:

Square recessed downlight model KOMBIC 100 SQ by Lamp brand. Reflector made of recycled polycarbonate R-PC FR WHITE TM non-brominated flame retardant additive. Flammability grade V0 according to UL94. Interior reflector and frame in white finish. Heatsink made of die-cast aluminium. COB LED, colour temperature 3000K with CR90. Luminaire with electronic wiring Dali included. Insolation Class II. Lifetime: 50.000 L70 B10. With IP43 degree of protection. Group 0 photobiological safety. With Wide Flood optics to achieve a controlled light distribution and low UGR<19.

Finish: Matte white RAL 9010


Weight: 442 g

Installation: Recessed

TECHNICAL SPECIFICATIONS:

Light output:	1.466 lm	°K :	3000
Plum:	20,3W	CRI :	90
Efficacy:	72,2 lm/w	R9 :	60
UGR:	<19	MacAdam:	3
Type:	COB	Power Supply:	220-240V 50/60Hz
LED Lifetime:	50.000 L80 B10 (Ta=25°C)	Gear:	Adjustable DALI
Power:	17W		

Light output tolerance +/- 10%



CUSTOM MADE OPTIONS:



KOMBIC 100 DOWNLIGHT

K11SQ2040WF930DWW

KOMBIC 100 SQ 2000 IP43 9WW WFL DA WH/WH

PHOTOMETRIC DATA :

K11SQ2040WF930DWW
 $\eta = 100\%$
 $I_{max} = 1238 \text{ cd/klm}$
 UTE: 1,00A
 CIE: 96 100 100 100 100

