Product datasheet

KOMBIC 100 DOWNLIGHT

LAMP
Worktitude for light

K11SQ2040WF930NBB — **KOMBIC 100 SQ 2000 IP43 9WW WFL BK/BK**

Description:

Finish: Matte black RAL 9011

TECHNICAL SPECIFICATIONS:

Light output:	1.410 lm	**ºK :**	3000
Plum:	14W	**CRI :**	90
Efficacy:	100,7 lm/w	**R9 :**	66
UGR:	<19		
Type:	COB		
LED Lifetime:	>100.000h L90 B10 (Ta=25ºC)		
Power:	12,2W		

Light output tolerance +/- 10%

IP
20 INT
43 EXT

EPD

CUSTOM MADE OPTIONS:

1-10V | ◐ | ▭ | ✱ | ↑lm | LED RETAIL | ⊕ | PUSH | TRIAC | K

03-06-2025

LAMP
Worktitude for light

K11SQ2040WF930NBB   **KOMBIC 100 SQ 2000 IP43 9WW WFL BK/BK**

PHOTOMETRIC DATA :

K11SQ2040WF930NBB

η = 100%

Imax = 1274 cd/klm

UTE:

CIE: 98 100 100 100 100

alpha = 57,1º

BACK   FRONT

50,1 %   50,1 %

Melanopic Lux Ratio: 0.573

Rf 90.3 – Rg 97.5

LAMP reserves the right to change the technical specifications of their products. These changes will allow the continual improvement of the products and will also ensure the conformity to current legal changes. Updated information is always available in our website www.lamp.es

Data according to regulations 2019/2020/EU and 2019/2015/EU