


**K11SQ2040WF940DWW**



**KOMBIC 100 SQ 2000 IP43 9NW WFL DA WH/WH**

**Description:**

Square recessed downlight model KOMBIC 100 SQ by Lamp brand. Reflector made of recycled polycarbonate R-PC FR WHITE TM non-brominated flame retardant additive. Flammability grade V0 according to UL94. Interior reflector and frame in white finish. Heatsink made of die-cast aluminium. COB LED, colour temperature 4000K with CR90. Luminaire with electronic wiring Dali included. Insolation Class II. Lifetime: 50.000 L70 B10. With IP43 degree of protection. Group 0 photobiological safety. With Wide Flood optics to achieve a controlled light distribution and low UGR<19. Environmental Product Declaration - EPD®available, according to UNE-EN ISO 9001:2015 and UNE-EN ISO 14001:2015.

**Finish:** Matte white RAL 9010


**Weight:** 442 g

**Installation:** Recessed

### TECHNICAL SPECIFICATIONS:

<b>Light output:</b>	1.519 lm	<b>%K :</b>	4000
<b>Plum:</b>	14W	<b>CRI :</b>	90
<b>Efficacy:</b>	108,5 lm/w	<b>R9 :</b>	59
<b>UGR:</b>	<19	<b>MacAdam:</b>	3
<b>Type:</b>	COB	<b>Power Supply:</b>	220-240V 50/60Hz
<b>LED Lifetime:</b>	>100.000h L90 B10 (Ta=25°C)	<b>Gear:</b>	Adjustable DALI
<b>Power:</b>	12,2W		

**Light output tolerance +/- 10%**



**CUSTOM MADE OPTIONS:**



KOMBIC 100 DOWNLIGHT

K11SQ2040WF940DWW

KOMBIC 100 SQ 2000 IP43 9NW WFL DA WH/WH

PHOTOMETRIC DATA :

