


KOMBIC 100 DOWNLIGHT

K11SQ2040WF940NMW



KOMBIC 100 SQ 2000 IP43 9NW WFL MA/WH

Description:

Square recessed downlight model KOMBIC 100 SQ by Lamp brand. Reflector made of recycled polycarbonate R-PC FR WHITE TM non-brominated flame retardant additive. Flammability grade V0 according to UL94. Matte metallic interior reflector and frame in white finish. Heatsink made of die-cast aluminium. COB LED, colour temperature 4000K with CR90. Luminaire with electronic wiring included. Insolation Class II. Lifetime: 50.000 L70 B10. With IP43 degree of protection. Group 0 photobiological safety. With Wide Flood optics to achieve a controlled light distribution and low glare level, less than UGR 17. Environmental Product Declaration - EPD@available, according to UNE-EN ISO 9001:2015 and UNE-EN ISO 14001:2015.

Finish: metalized polycarbonate mate


Weight: 382 g

Installation: Recessed

TECHNICAL SPECIFICATIONS:

Light output:	1.504 lm	°K :	4000
Plum:	14W	CRI :	90
Efficacy:	107,4 lm/w	R9 :	59
UGR:	<19	MacAdam:	3
Type:	COB	Power Supply:	220-240V 50-60Hz
LED Lifetime:	>100.000h L90 B10 (Ta=25°C)	Gear:	Electronic
Power:	12,2W		

Light output tolerance +/- 10%



CUSTOM MADE OPTIONS:



KOMBIC 100 DOWNLIGHT

K11SQ2040WF940NMW

KOMBIC 100 SQ 2000 IP43 9NW WFL MA/WH

PHOTOMETRIC DATA :

