Product datasheet

KOMBIC 100 DOWNLIGHT

LAMP
Worktitude for light

K11SQ2040WFWB4NMW — **KOMBIC 100 SQ 1800 IP43 WBN WFL MA/WH**

Description:

Finish: metalized polycarbonate mate

TECHNICAL SPECIFICATIONS:

Light output:	1.756 lm		**ºK :**	4000
Plum:	19,5W		**CRI :**	95
Efficacy:	89,1 lm/w		**R9 :**	91
UGR:	<19			
LED Lifetime:	86.000h L80 B10 (Ta=25ºC)			
Power:	17,2W			

Light output tolerance +/- 10%

IP
20 INT
43 EXT

EPD

CUSTOM MADE OPTIONS:

1-10V   ◐   ▥   ✳   ↑lm   LED RETAIL   ⊕   PUSH   TRIAC   K

K11SQ2040WFWB4NMW   **KOMBIC 100 SQ 1800 IP43 WBN WFL MA/WH**

PHOTOMETRIC DATA :

K11SQ2040WFWB4NMW

η = 100%

Imax = 1290 cd/klm

UTE: 1,00A

CIE: 96 99 100 100 100

alpha = 56,2º

BACK   FRONT

50,1 %   50,1 %

Melanopic Lux Ratio: 0.765

Rf 97.6 – Rg 99.3

Tel.   +34937366800

Web   www.lamp.es

LAMP reserves the right to change the technical specifications of their products. These changes will allow the continual improvement of the products and will also ensure the conformity to current legal changes. Updated information is always available in our website www.lamp.es

03-06-2025

Pág.   2 / 2

Data according to regulations 2019/2020/EU and 2019/2015/EU