Product datasheet

KOMBIC 100 DOWNLIGHT

LAMP
Worktitude for light

K11SQ2040WFWB4NWW – **KOMBIC 100 SQ 1800 IP43 WBN WFL WH/WH**

Description:

Finish: Matte white RAL 9010

TECHNICAL SPECIFICATIONS:

Light output:	1.756 lm	**ºK :**	4000
Plum:	19,5W	**CRI :**	95
Efficacy:	89,1 lm/w	**R9 :**	91
UGR:	<19		
LED Lifetime:	86.000h L80 B10 (Ta=25ºC)		
Power:	17,2W		

Light output tolerance +/- 10%

IP
20 INT
43 EXT

EPD

CUSTOM MADE OPTIONS:

1-10V | | ••• | ✳ | ↑lm | LED RETAIL | | PUSH | TRIAC | K

LAMP
Worktitude for light

K11SQ2040WFWB4NWW   KOMBIC 100 SQ 1800 IP43 WBN WFL WH/WH

PHOTOMETRIC DATA :

K11SQ2040WFWB4NWW

η = 100%

Imax = 1290 cd/klm

UTE: 1,00A

CIE: 96 99 100 100 100

alpha = 56,2º

BACK   FRONT

50,1 %   50,1 %

Melanopic Lux Ratio: 0.765

Rf

1 - Limits on the Planckian locus

Rg

2 - Limits for practical sources

Rf 97.6 - Rg 99.3

03-06-2025

Data according to regulations 2019/2020/EU and 2019/2015/EU