


KOMBIC 100 DOWNLIGHT

K11SQ2043WW830NBB

- KOMBIC 100 SQ 2000 IP43 WW WW BK/BK



Description:

LAMP Square recessed downlight KOMBIC 100 SQ 2000 Reflector made of recycled polycarbonate R-PC FR WHITE TM non-brominated flame retardant additive. Flammability grade V0 according to UL94. Inner reflector finished in Wallwasher optic option, suitable for vertical plane lighting or work areas surroundings. Heatsink made of die-cast aluminium with black finish. COB LED, colour temperature 3000K and CRI80. Electronic ON OFF gear included. IP43 rated. Insulation Class II. Photobiological safety group 0. LED life time: 50. 000 L90 B10. Available finishes: White and black. Environmental Product Declaration - EPD®available, according to UNE-EN ISO 9001:2015 and UNE-EN ISO 14001:2015.

Finish: Matte black RAL 9011


Weight: 517 g

Installation: Recessed

TECHNICAL SPECIFICATIONS:

Light output:	1.159 lmw	°K :	3000
Plum:	13,7W	CRI :	80
Efficacy:	84,6 lm/w	MacAdam:	3
Type:	COB	Power Supply:	220-240V 50/60Hz
LED Lifetime:	50.000 L90 B10 (Ta=25°C)	Gear:	Electronic
Power:	13W		

Light output tolerance +/- 10%



CUSTOM MADE OPTIONS:



KOMBIC 100 DOWNLIGHT

K11SQ2043WW830NBB

KOMBIC 100 SQ 2000 IP43 WW WW BK/BK

PHOTOMETRIC DATA :

