


KOMBIC 100 DOWNLIGHT

K11SQ25400P830NRW



KOMBIC 100 SQ 2500 IP43 WW OPAL BR/WH

Description:

Square recessed downlight model KOMBIC 100 SQ by Lamp brand. Reflector made of recycled polycarbonate R-PC FR WHITE TM non-brominated flame retardant additive. Flammability grade V0 according to UL94. Shiny metalized interior reflector and frame in white finish and optical film. Heatsink made of die-cast aluminium. COB LED, colour temperature 3000K with CRI80. Luminaire with electronic wiring included. Insolation Class II. Lifetime: 50.000 L80 B10. With IP43 degree of protection. Group 0 photobiological safety. Environmental Product Declaration - EPD@available, according to UNE-EN ISO 9001:2015 and UNE-EN ISO 14001:2015.

Finish: BRILLIANT METALLIC POLYCARBONATE


Weight: 392 g

Installation: Recessed

TECHNICAL SPECIFICATIONS:

Light output:	1.994 lm	°K :	3000
Plum:	19,1W	CRI :	80
Efficacy:	104,4 lm/w	MacAdam:	3
Type:	COB	Power Supply:	220-240V 50/60Hz
LED Lifetime:	50.000 L80 B10 (Ta=25°C)	Gear:	Electronic
Power:	17W		

Light output tolerance +/- 10%



CUSTOM MADE OPTIONS:



KOMBIC 100 DOWNLIGHT

K11SQ25400P830NRW

KOMBIC 100 SQ 2500 IP43 WW OPAL BR/WH

PHOTOMETRIC DATA :

