KOMBIC 100 SUT



K11ST1523RF927DBB

- KOM 100 SUT 1500 IP23 9VWW RF FL DA B/B

| Description: | | | | |
|--------------------------------|--------------------------|---------------|------------------|--|
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| Weight: 712 g | | | | |
| Installation: Recessed | | | | |
| | | | | |
| TECHNICAL SPECIFICATIONS: | | | | |
| Light output: | 1.273 lm | °К: | 2700 | |
| Plum: | 13,9W | CRI: | 90 | |
| Efficacy: | 107,3 lm/w | R9: | 58 | |
| UGR: | <19 | MacAdam: | 3 | |
| Туре: | COB | Power Supply: | 220-240V 50/60Hz | |
| LED Lifetime: | 50.000 L80 B10 (Ta=25°C) | Gear: | Adjustable DALI | |
| Power: | 13W | | | |
| Light output tolerance +/- 10% | | | | |
| | | | | |
| | | | | |
| EPD | | | | |
| | | | | |
| | | | | |
| | | | | |
| CUSTOM MADE OPTIONS: | | | | |
| RAW | | | | |



KOMBIC 100 SUT



K11ST1523RF927DBB

KOM 100 SUT 1500 IP23 9VWW RF FL DA B/B

PHOTOMETRIC DATA:

K11ST1523RF927DBB $\eta = 100\%$ Imax = 2279 cd/klm UTE:

CIE: 100 100 100 100 100















