KOMBIC 100 SUT


K11ST1540WF927NBW



KOMBIC 100 SUT 1500 IP40 9VWW WFL BK/WH.

Description:

Suspended track mounting downlight model KOMBIC 100 SUT by Lamp brand. Body made of white aluminum extrusion with reflector made of recycled polycarbonate R-PC FR WHITE TM non-brominated flame retardant additive. Flammability grade V0 according to UL94. Black interior reflector. Heatsink made of die-cast aluminium. COB LED, colour temperature 2700K with CRI90. Luminaire with electronic wiring included. Insolation Class I. Lifetime: >100.000 L90 B10. With IP40 degree of protection. Group 0 photobiological safety. With Wide Flood optics to achieve a controlled light distribution and low glare level, less than UGR<19. Environmental Product Declaration - EPD®available, according to UNE-EN ISO 9001:2015 and UNE-EN ISO 14001:2015.



Finish: Matte black RAL 9011

TECHNICAL SPECIFICATIONS:

Light output: 1.002 lm °K: 2700 Plum: 10W CRI: 90 Efficacy: 100,2 lm/w R9: 57

UGR:

LED Lifetime: >100.000h L90 B10 (Ta=25°C)

8,5W Power:

Light output tolerance +/- 10%

























CUSTOM MADE OPTIONS:



KOMBIC 100 SUT



K11ST1540WF927NBW

KOMBIC 100 SUT 1500 IP40 9VWW WFL BK/WH.

PHOTOMETRIC DATA:

K11ST1540WF927NBW η = 100% lmax = 1274 cd/klmUTE: CIE: 98 100 100 100 100

