


## KOMBIC 100 SUT

K11ST1540WF927NMW




## - KOMBIC 100 SUT 1500 IP40 9VWW WFL MA/WH.

**Description:**

Suspended track mounting downlight model KOMBIC 100 SUT by Lamp brand. Body made of white aluminum extrusion with reflector made of recycled polycarbonate R-PC FR WHITE TM non-brominated flame retardant additive. Flammability grade V0 according to UL94. Matte metallic interior reflector. Heatsink made of die-cast aluminium. COB LED, colour temperature 2700K with CRI90. Luminaire with electronic wiring included. Insolation Class I. Lifetime: >100.000 L90 B10. With IP40 degree of protection. Group 0 photobiological safety. With Wide Flood optics to achieve a controlled light distribution and low glare level, less than UGR<19. Environmental Product Declaration - EPD@available, according to UNE-EN ISO 9001:2015 and UNE-EN ISO 14001:2015.

**Finish:** metalized polycarbonate mate
**TECHNICAL SPECIFICATIONS:**

<b>Light output:</b>	1.034 lm	<b>°K :</b>	2700
<b>Plum:</b>	10W	<b>CRI :</b>	90
<b>Efficacy:</b>	103,4 lm/w	<b>R9 :</b>	57
<b>UGR:</b>	<19		
<b>LED Lifetime:</b>	>100.000h L90 B10 (Ta=25°C)		
<b>Power:</b>	8,5W		

*Light output tolerance +/- 10%*
**CUSTOM MADE OPTIONS:**

K11ST1540WF927NMW

KOMBIC 100 SUT 1500 IP40 9VWW WFL MA/WH.

**PHOTOMETRIC DATA :**

