

KOMBIC 100 SUT


K11ST1540WF930NMB




- KOMBIC 100 SUT 1500 IP40 9WW WFL MA/BK.

Description:

Suspended track mounting downlight model KOMBIC 100 SUT by Lamp brand. Body made of black aluminum extrusion with reflector made of recycled polycarbonate R-PC FR WHITE TM non-brominated flame retardant additive. Flammability grade V0 according to UL94. Matte metallic interior reflector. Heatsink made of die-cast aluminium. COB LED, colour temperature 3000K with CRI90. Luminaire with electronic wiring included. Insolation Class I. Lifetime: >100.000 L90 B10. With IP40 degree of protection. Group 0 photobiological safety. With Wide Flood optics to achieve a controlled light distribution and low glare level, less than UGR<19. Environmental Product Declaration - EPD@available, according to UNE-EN ISO 9001:2015 and UNE-EN ISO 14001:2015.

Finish: metalized polycarbonate mate
**TECHNICAL SPECIFICATIONS:**

Light output:	1.088 lm	°K :	3000
Plum:	10W	CRI :	90
Efficacy:	108,8 lm/w	R9 :	66
UGR:	<19		
LED Lifetime:	>100.000h L90 B10 (Ta=25°C)		
Power:	8,5W		

Light output tolerance +/- 10%
**CUSTOM MADE OPTIONS:**

K11ST1540WF930NMB

KOMBIC 100 SUT 1500 IP40 9WW WFL MA/BK.

PHOTOMETRIC DATA :

