1000

120

Ø100mm

# KOMBIC 100 SUT

## K11ST1540WF940NWB

#### KOMBIC 100 SUT 1500 IP40 9NW WFL WH/BK.

#### Description:

Suspended track mounting downlight model KOMBIC 100 SUT by Lamp brand. Body made of black aluminum extrusion with reflector made of recycled polycarbonate R-PC FR WHITE TM non-brominated flame retardant additive. Flammability grade V0 according to UL94. White interior reflector. Heatsink made of die-cast aluminium. COB LED, colour temperature 4000K with CRI90. Luminaire with electronic wiring included. Insolation Class I. Lifetime: >100.000 L90 B10. With IP40 degree of protection. Group 0 photobiological safety. With Wide Flood optics to achieve a controlled light distribution and low UGR<19. Environmental Product Declaration - EPD®available, according to UNE-EN ISO 9001:2015 and UNE-EN ISO 14001:2015.

Finish: Matte white RAL 9010

#### **TECHNICAL SPECIFICATIONS:**

| Light output: | 1.134 lm                    | ٩ <b>κ</b> : | 4000 |
|---------------|-----------------------------|--------------|------|
| Plum:         | 10W                         | CRI :        | 90   |
| Efficacy:     | 113,4 lm/w                  | R9 :         | 59   |
| UGR:          | <19                         |              |      |
| LED Lifetime: | >100.000h L90 B10 (Ta=25°C) |              |      |
| Power:        | 8,5W                        |              |      |

#### Light output tolerance +/- 10%



## **CUSTOM MADE OPTIONS:**



Worktitude for light

## **KOMBIC 100 SUT**

K11ST1540WF940NWB

KOMBIC 100 SUT 1500 IP40 9NW WFL WH/BK.



### **PHOTOMETRIC DATA :**



