**Product datasheet**

# KOMBIC 100 SUT

**Worktitude for light**

**K11ST1540WFWB4NMW** **-** **KOMBIC 100 SUT 1200 IP40 WBN WFL MA/WH.**

**Description:**

1000

120

ø100mm

**Finish:** metalized polycarbonate mate

**TECHNICAL SPECIFICATIONS:**

**R9 :** 91

| AI | CLASE I | IP 40 | LED 4000ºK | PC | 650º |
|---|---|---|---|---|---|

| CE | EPD | GARANTIA 5 WARRANTY GARANTIE | Group 0 En 62471 |
|---|---|---|---|

**CUSTOM MADE OPTIONS:**

**RAW**

**LAMP**
**Worktitude for light**

**K11ST1540WFWB4NMW**          **KOMBIC 100 SUT 1200 IP40 WBN WFL MA/WH.**

## PHOTOMETRIC DATA :





**Melanopic Lux Ratio: 0.776**





**Rf 96.1 – Rg 98.7**

LAMP reserves the right to change the technical specifications of their products. These changes will allow the continual improvement of the products and will also ensure the conformity to current legal changes. Updated information is always available in our website www.lamp.es

18-07-2025

Pág.    2 / 2

Data according to regulations 2019/2020/EU and 2019/2015/EU