KOMBIC 100 SUT



K11ST2023RF830DWB

- KOMBIC 100 SUT 2000 IP23 WW RF FL DA W/B

Description:

Finish: Matte white RAL 9010

Weight: 712 g

Installation: Suspended

TECHNICAL SPECIFICATIONS:

Light output: 1.612 lm °K: 3000 Plum: 13,9W CRI: 80 Efficacy: 115,9 lm/w R9: 80 UGR: <19 3 MacAdam:

 Type:
 COB
 Power Supply:
 220-240V 50/60Hz

 LED Lifetime:
 50.000 L80 B10 (Ta=25°C)
 Gear:
 Adjustable DALI

Power: 13W

Light output tolerance +/- 10%

EPD

KOMBIC 100 SUT





K11ST2023RF830DWB


KOMBIC 100 SUT 2000 IP23 WW RF FL DA W/B

PHOTOMETRIC DATA:

$$\label{eq:control_problem} \begin{split} &\text{K11ST2023RF830DWB} \\ &\eta = 100\% \\ &\text{Imax} = 2200 \text{ cd/klm} \\ &\text{UTE:} \\ &\text{CIE: } 98 \text{ } 99 \text{ } 100 \text{ } 100 \text{ } 100 \end{split}$$







Data according to regulations 2019/2020/EU and 2019/2015/EU