KOMBIC 100 SUT



K11ST2023RF830NBB

KOMBIC 100 SUT 2000 IP23 WW RF FL BK/BK

Description:

Finish: Matte black RAL 9011

Weight: 502 g

Installation: Suspended

TECHNICAL SPECIFICATIONS:

Light output: 1.549 lm °K: 3000 Plum: 14,1W CRI: 80 Efficacy: 115,9 lm/w R9: 80 UGR: <19

MacAdam: 3 Type: СОВ

LED Lifetime: 50.000 L80 B10 (Ta=25°C) Gear: Electronic

Power Supply:

220-240V 50/60Hz

Power: 13W

Light output tolerance +/- 10%

EPD

KOMBIC 100 SUT





K11ST2023RF830NBB


KOMBIC 100 SUT 2000 IP23 WW RF FL BK/BK

PHOTOMETRIC DATA:

$$\label{eq:continuous} \begin{split} &\text{K11ST2023RF830NBB} \\ &\eta = 100\% \\ &\text{Imax} = 2279 \text{ cd/klm} \\ &\text{UTE:} \\ &\text{CIE:} \ 100 \ 100 \ 100 \ 100 \ 100 \ 100 \end{split}$$







Data according to regulations 2019/2020/EU and 2019/2015/EU