KOMBIC 100 SUT

K11ST2023RF840DWW



KOMBIC 100 SUT 2000 IP23 NW RF FL DA W/W


Description:

Suspended track mounting downlight model KOMBIC 100 SUT by Lamp brand. Body made of white aluminum extrusion with reflector made of recycled polycarbonate R-PC FR WHITE TM non-brominated flame retardant additive. Flammability grade V0 according to UL94. White interior reflector and optical film. Heatsink made of diecast aluminium. COB LED, colour temperature 4000K with CRI80. Luminaire with electronic wiring Dali included. Insolation Class I. Lifetime: 50.000 L80 B10. With IP23 degree of protection. Group 0 photobiological safety. Reflector aluminium Flood to achieve a controlled light distribution. Environmental Product Declaration -EPD®available, according to UNE-EN ISO 9001:2015 and UNE-EN ISO 14001:2015.

Finish: Matte white RAL 9010

Weight: 712 g

Installation: Suspended



TECHNICAL SPECIFICATIONS:

Light output: 1.692 lm °K: 4000 Plum: 13,9W CRI: 80 Efficacy: 121,7 lm/w R9: 80 UGR: <19 MacAdam: 3

Type: СОВ Power Supply: 220-240V 50/60Hz LED Lifetime: 50.000 L80 B10 (Ta=25°C) Gear: Adjustable DALI

13W Power:

Light output tolerance +/- 10%



























CUSTOM MADE OPTIONS:









Data according to regulations 2019/2020/EU and 2019/2015/EU













KOMBIC 100 SUT





K11ST2023RF840DWW


KOMBIC 100 SUT 2000 IP23 NW RF FL DA W/W

PHOTOMETRIC DATA:

$$\label{eq:continuous} \begin{split} &\text{K11ST2023RF840DWW} \\ &\eta = 100\% \\ &\text{Imax} = 2200 \text{ cd/klm} \\ &\text{UTE:} \\ &\text{CIE: } 98 \ 99 \ 100 \ 100 \ 100 \end{split}$$







Data according to regulations 2019/2020/EU and 2019/2015/EU