#### **KOMBIC 100 SUT**

#### K11ST2023RF840NWW



#### KOMBIC 100 SUT 2000 IP23 NW RF FL WH/WH

#### Description:

Suspended track mounting downlight model KOMBIC 100 SUT by Lamp brand. Body made of white aluminum extrusion with reflector made of recycled polycarbonate R-PC FR WHITE TM non-brominated flame retardant additive. Flammability grade V0 according to UL94. White interior reflector. Heatsink made of die-cast aluminium. COB LED, colour temperature 4000K with CRI80. Luminaire with electronic wiring included. Insolation Class I. Lifetime: 50.000 L80 B10. With IP23 degree of protection. Group 0 photobiological safety. Reflector aluminium Flood to achieve a controlled light distribution. Environmental Product Declaration - EPD®available, according to UNE-EN ISO 9001:2015 and UNE-EN ISO 14001:2015.



Finish: Matte white RAL 9010

Weight: 502 g

Installation: Suspended

#### **TECHNICAL SPECIFICATIONS:**

Light output: 1.692 lm °K: 4000 Plum: 14,1W CRI: 80 Efficacy: 120 lm/w R9: 80 UGR: <19 MacAdam: 3

Type: СОВ Power Supply: 220-240V 50/60Hz

LED Lifetime: 50.000 L80 B10 (Ta=25°C) Gear: Electronic

13W Power:

### Light output tolerance +/- 10%





























## **CUSTOM MADE OPTIONS:**









Data according to regulations 2019/2020/EU and 2019/2015/EU











# **KOMBIC 100 SUT**



K11ST2023RF840NWW

# KOMBIC 100 SUT 2000 IP23 NW RF FL WH/WH

### **PHOTOMETRIC DATA:**

K11ST2023RF840NWW  $\eta$  = 100% Imax = 2200 cd/klm UTE: CIE: 98 99 100 100 100





