KOMBIC 100 SUT

LAMP
Worktitude for light

K11ST2023RW830DBB — **KOM 100 SUT 2000 IP23 WW RF WFL DA BK/BK**

Description:

Finish: Matte black RAL 9011

Weight: 712 g

Installation: Suspended

TECHNICAL SPECIFICATIONS:

Light output:	1.421 lm	**ºK :**	3000
Plum:	13,9W	**CRI :**	80
Efficacy:	102,2 lm/w	**MacAdam:**	3
UGR:	<19	**Power Supply:**	220-240V 50/60Hz
Type:	COB	**Gear:**	Adjustable DALI
LED Lifetime:	50.000 L80 B10 (Ta=25ºC)		
Power:	13W		

Light output tolerance +/- 10%

EPD

CUSTOM MADE OPTIONS:

RAW

KOMBIC 100 SUT

LAMP
Worktitude for light

K11ST2023RW830DBB   **KOM 100 SUT 2000 IP23 WW RF WFL DA BK/BK**

PHOTOMETRIC DATA :

K11ST2023RW830DBB

η = 100%

Imax = 1293 cd/klm

UTE:

CIE: 99 100 100 100 100

alpha = 59,5°

BACK   FRONT

49,9 %   49,9 %

15-05-2025

Data according to regulations 2019/2020/EU and 2019/2015/EU