KOMBIC 100 SUT



K11ST2023RW840DWB

- I	KOM	100	SUT	2000	IP23	NW	RF	WFL	. DA	WH/BK	Ĺ
-----	-----	-----	-----	------	------	----	----	-----	------	-------	---

110111 100 001 2	OOO II 23 NW KI WI L DA WI											
Description:												
Finish: Matte black RAL 9011												
Weight: 712 g												
Installation: So	uspended											
TECHNICAL SP	ECIFICATIONS:											
Light output:	1.614 lm	°K :	4000									
Plum:	13,9W	CRI:	80									
Efficacy:	116,1 lm/w	MacAdam:	3									
Туре:	СОВ	Power Supply:	220-240V 50/60Hz									
LED Lifetime:	50.000 L80 B10 (Ta=25°C)	Gear:	Adjustable DALI									
Power:	13W											
Light output toler	ance +/- 10%											
EPD												
CUSTOM MADE	E OPTIONS:											
RAW												
()												



KOMBIC 100 SUT



K11ST2023RW840DWB

KOM 100 SUT 2000 IP23 NW RF WFL DA WH/BK

PHOTOMETRIC DATA:


K11ST2023RW840DWB η = 100%


lmax = 1215 cd/klm


UTE: 1,00A

CIE: 94 97 99 100 100









Data according to regulations 2019/2020/EU and 2019/2015/EU