#### **Product datasheet**

#### **KOMBIC 100 SUT**


#### K11ST2023RW840NWW



#### KOMBIC 100 SUT 2000 IP23 NW RF WFL WH/WH

#### Description:

Suspended track mounting downlight model KOMBIC 100 SUT by Lamp brand. Body made of white aluminum extrusion with reflector made of recycled polycarbonate R-PC FR WHITE TM non-brominated flame retardant additive. Flammability grade V0 according to UL94. White interior reflector. Heatsink made of die-cast aluminium. COB LED, colour temperature 4000K with CRI80. Luminaire with electronic wiring included. Insolation Class I. Lifetime: 50.000 L80 B10. With IP23 degree of protection. Group 0 photobiological safety. Reflector aluminium Wide Flood to achieve a controlled light distribution. Environmental Product Declaration - EPD®available, according to UNE-EN ISO 9001:2015 and UNE-EN ISO 14001:2015.



Finish: Matte white RAL 9010

Weight: 502 g

Installation: Suspended

#### **TECHNICAL SPECIFICATIONS:**

Light output: 1.614 lm °K: 4000 Plum: 14,1W CRI: 80 Efficacy: 114,4 lm/w 3 MacAdam:

Type: СОВ Power Supply: 220-240V 50/60Hz

LED Lifetime: 50.000 L80 B10 (Ta=25°C) Gear: Electronic

13W Power:

#### Light output tolerance +/- 10%



























# **CUSTOM MADE OPTIONS:**









Data according to regulations 2019/2020/EU and 2019/2015/EU











## **KOMBIC 100 SUT**



K11ST2023RW840NWW

## KOMBIC 100 SUT 2000 IP23 NW RF WFL WH/WH

#### **PHOTOMETRIC DATA:**

$$\label{eq:control_control_control} \begin{split} \text{K11ST2023RW840NWW} \\ \eta &= 100\% \\ \text{Imax} &= 1215 \text{ cd/klm} \end{split}$$

UTE: 1,00A

CIE: 94 97 99 100 100

