## **KOMBIC 100 SUT**



K11ST2023RW930NWW

Description:				
Finish: Matte	white RAL 9010			
Weight: 502 g				
	Nonended			
Installation: §	suspended			
Installation: S	suspended			
	PECIFICATIONS:			
FECHNICAL SF		°K:	3000	
FECHNICAL SF	PECIFICATIONS:	°K : CRI :	3000 90	
FECHNICAL SF Light output: Plum:	PECIFICATIONS:			
FECHNICAL SF Light output: Plum: Efficacy:	PECIFICATIONS:  1.784 lm  21,6W	CRI:	90	
FECHNICAL SF Light output: Plum: Efficacy: Type:	PECIFICATIONS:  1.784 lm  21,6W  82,5 lm/w	CRI : R9 : MacAdam:	90 53	
TECHNICAL SI Light output: Plum: Efficacy: Type: LED Lifetime:	PECIFICATIONS:  1.784 lm  21,6W  82,5 lm/w  COB	CRI : R9 : MacAdam:	90 53 3	
FECHNICAL SE Light output: Plum: Efficacy: Type: LED Lifetime:	PECIFICATIONS:  1.784 lm  21,6W  82,5 lm/w  COB  50.000 L80 B10 (Ta=25°C)	CRI : R9 : MacAdam: Power Supply:	90 53 3 220-240V 50/60Hz	
TECHNICAL SF Light output: Plum: Efficacy: Type: LED Lifetime: Power:	PECIFICATIONS:  1.784 lm  21,6W  82,5 lm/w  COB  50.000 L80 B10 (Ta=25°C)  13W	CRI : R9 : MacAdam: Power Supply:	90 53 3 220-240V 50/60Hz	



# **CUSTOM MADE OPTIONS:**



#### **KOMBIC 100 SUT**



K11ST2023RW930NWW

### **KOMBIC 100 SUT 2000 IP23 9WW RF WFL W/W**

#### **PHOTOMETRIC DATA:**

K11ST2023RW930NWW  $\eta = 100\%$ 

Imax = 1215 cd/klm

UTE: 1,00A

CIE: 94 97 99 100 100















