KOMBIC 100 SUT

K11ST2023RW940NMW

-	KOMBIC	100 SUT	2000 IP2	23 9NW RF	WFL M/W
---	--------	---------	----------	-----------	---------

INDIA 100 O	31 2000 11 23 3NW IN WI E 111/W								
Description:									
Finish: Matte Traffic white RAL 9016									
Weight: 502 g									
Installation: Suspended									
TECHNICAL CD	FCIFICATIONS:								
TECHNICAL SP	ECIFICATIONS:								
Light output:	1.902 lm	⁰K :	4000						
Plum:	21,6W	CRI:	90						
Efficacy:	88 lm/w	R9:	65						
Туре:	COB	MacAdam:	3						
LED Lifetime:	50.000 L80 B10 (Ta=25°C)	Power Supply:							
Power:	13W	Gear:	Electronic						
Light output toler	anaa . / 109/								
Light output toler	ance +/- 10%								
EDD									
EPD									
CUSTOM MADE	E OPTIONS:								
PAW.									



KOMBIC 100 SUT



K11ST2023RW940NMW

KOMBIC 100 SUT 2000 IP23 9NW RF WFL M/W

PHOTOMETRIC DATA:

K11ST2023RW940NMW

 $\eta = 100\%$

Imax = 1215 cd/klm

UTE: 1,00A

CIE: 94 97 99 100 100















