#### **Product datasheet**

# **KOMBIC 100 SUT**

### K11ST2040OP830NWW





#### KOMBIC 100 SUT 2000 IP40 WW OP WH/WH

#### **Description:**

Suspended track mounting downlight model KOMBIC 100 SUT by Lamp brand. Body made of white aluminum extrusion with reflector made of recycled polycarbonate R-PC FR WHITE TM non-brominated flame retardant additive. Flammability grade V0 according to UL94. White interior reflector and optical film. Heatsink made of diecast aluminium. COB LED, colour temperature 3000K with CRI80. Luminaire with electronic wiring included. Insolation Class I. Lifetime: 50.000 L80 B10. With IP40 degree of protection. Group 0 photobiological safety. Environmental Product Declaration - EPD®available, according to UNE-EN ISO 9001:2015 and UNE-EN ISO 14001:2015.

Finish: Matte white RAL 9010

Installation: Suspended

#### **TECHNICAL SPECIFICATIONS:**

Light output:	1.454 lm	<b>°K</b> :	3000
Plum:	13,4W	CRI :	80
Efficacy:	108,5 lm/w	MacAdam:	3
Туре:	СОВ	Power Supply:	220-240V 50/60Hz
LED Lifetime:	50.000 L80 B10 (Ta=25ºC)	Gear:	Electronic
Power:	12W		

#### Light output tolerance +/- 10%



## CUSTOM MADE OPTIONS:



Worktitude for light

# **KOMBIC 100 SUT**

K11ST2040OP830NWW

KOMBIC 100 SUT 2000 IP40 WW OP WH/WH



### **PHOTOMETRIC DATA :**

