KOMBIC 100 SUT


K11ST2040OP840NWW



KOMBIC 100 SUT 2000 IP40 NW OP WH/WH

Description:

Suspended track mounting downlight model KOMBIC 100 SUT by Lamp brand. Body made of white aluminum extrusion with reflector made of recycled polycarbonate R-PC FR WHITE TM non-brominated flame retardant additive. Flammability grade V0 according to UL94. White interior reflector and optical film. Heatsink made of diecast aluminium. COB LED, colour temperature 3000K with CRI80. Luminaire with electronic wiring included. Insolation Class I. Lifetime: 50.000 L80 B10. With IP40 degree of protection. Group 0 photobiological safety. Environmental Product Declaration - EPD®available, according to UNE-EN ISO 9001:2015 and UNE-EN ISO 14001:2015.



Finish: Matte white RAL 9010

Installation: Suspended

TECHNICAL SPECIFICATIONS:

Light output: 1.541 lm °K: 4000 Plum: 13,4W CRI: 80 Efficacy: 115 lm/w 3 MacAdam:

Type: СОВ Power Supply: 220-240V 50/60Hz

LED Lifetime: 50.000 L80 B10 (Ta=25°C) Gear: Electronic

Power: 12W

Light output tolerance +/- 10%





























CUSTOM MADE OPTIONS:









Data according to regulations 2019/2020/EU and 2019/2015/EU













KOMBIC 100 SUT



K11ST2040OP840NWW

KOMBIC 100 SUT 2000 IP40 NW OP WH/WH

PHOTOMETRIC DATA:

K11ST2040OP840NWW η = 100% lmax = 787 cd/klmUTE: 1,00B

