


KOMBIC 100 SUT

K11ST2040OP940NWW



KOMBIC 100 SUT 2000 IP40 9NW OP WH/WH.

Description:

Suspended track mounting downlight model KOMBIC 100 SUT by Lamp brand. Body made of white aluminum extrusion with reflector made of recycled polycarbonate R-PC FR WHITE TM non-brominated flame retardant additive. Flammability grade V0 according to UL94. White interior reflector and optical film. Heatsink made of die-cast aluminium. COB LED, colour temperature 3000K with CRI90. Luminaire with electronic wiring included. Insolation Class I. Lifetime: 50.000 L80 B10. With IP40 degree of protection. Group 0 photobiological safety. Environmental Product Declaration - EPD@available, according to UNE-EN ISO 9001:2015 and UNE-EN ISO 14001:2015.

Finish: Matte white RAL 9010**Weight:** 676 g**Installation:** Surface**TECHNICAL SPECIFICATIONS:**

Light output:	1.785 lm	°K :	4000
Plum:	20,4W	CRI :	90
Efficacy:	87,5 lm/w	MacAdam:	3
Type:	COB	Power Supply:	220-240V 50/60Hz
LED Lifetime:	50.000 L80 B10 (Ta=25°C)	Gear:	Electronic
Power:	17W		

Light output tolerance +/- 10%**CUSTOM MADE OPTIONS:**

K11ST20400P940NWW

KOMBIC 100 SUT 2000 IP40 9NW OP WH/WH.

PHOTOMETRIC DATA :

