


KOMBIC 100 SUT

K11ST2040WF830DMB



KOMBIC 100 SUT 2000 IP40 WW WFL DA MA/BK

Description:

Suspended track mounting downlight model KOMBIC 100 SUT by Lamp brand. Body made of black aluminum extrusion with reflector made of recycled polycarbonate R-PC FR WHITE TM non-brominated flame retardant additive. Flammability grade V0 according to UL94. Matte metallic interior reflector. Heatsink made of die-cast aluminium. COB LED, colour temperature 3000K with CRI80. Luminaire with electronic wiring Dali included. Insulation Class I. Lifetime: 50.000 L80 B10. With IP40 degree of protection. Group 0 photobiological safety. With Wide Flood optics to achieve a controlled light distribution and low glare level, less than UGR 17. Environmental Product Declaration - EPD@available, according to UNE-EN ISO 9001:2015 and UNE-EN ISO 14001:2015.

Finish: metalized polycarbonate mate

Installation: Suspended
TECHNICAL SPECIFICATIONS:

| | | | |
|----------------------|--------------------------|----------------------|------------------|
| Light output: | 1.268 lm | °K : | 3000 |
| Plum: | 14,8W | CRI : | 80 |
| Efficacy: | 85,7 lm/w | MacAdam: | 3 |
| UGR: | <19 | Power Supply: | 220-240V 50/60Hz |
| Type: | COB | Gear: | Adjustable DALI |
| LED Lifetime: | 50.000 L80 B10 (Ta=25°C) | | |
| Power: | 12W | | |

Light output tolerance +/- 10%
**CUSTOM MADE OPTIONS:**

K11ST2040WF830DMB

KOMBIC 100 SUT 2000 IP40 WW WFL DA MA/BK

PHOTOMETRIC DATA :

