


KOMBIC 100 SUT

TECHNICAL DATA ON REVIEW

K11ST2040WF840NMB



KOMBIC 100 SUT 2000 IP40 NW WFL MA/BK.

Description:

Suspended track mounting downlight model KOMBIC 100 SUT by Lamp brand. Body made of black aluminum extrusion with reflector made of recycled polycarbonate R-PC FR WHITE TM non-brominated flame retardant additive. Flammability grade V0 according to UL94. Matte metallic interior reflector. Heatsink made of die-cast aluminium. COB LED, colour temperature 4000K with CRI80. Luminaire with electronic wiring included. Insolation Class I. Lifetime: 50.000 L80 B10. With IP40 degree of protection. Group 0 photobiological safety. With Wide Flood optics to achieve a controlled light distribution and low glare level, less than UGR 17. Environmental Product Declaration - EPD@available, according to UNE-EN ISO 9001:2015 and UNE-EN ISO 14001:2015.

Finish: metalized polycarbonate mate

Installation: Suspended

TECHNICAL SPECIFICATIONS:

Light output:	1.351 lm	°K :	4000
Plum:	14,5W	CRI :	80
Efficacy:	93,2 lm/w	MacAdam:	3
UGR:	<19	Power Supply:	220-240V 50/60Hz
Type:	COB	Gear:	Electronic
LED Lifetime:	50.000 L80 B10 (Ta=25°C)		
Power:	12W		

Light output tolerance +/- 10%


CUSTOM MADE OPTIONS:



KOMBIC 100 SUT

TECHNICAL DATA ON REVIEW

K11ST2040WF840NMB

KOMBIC 100 SUT 2000 IP40 NW WFL MA/BK.

PHOTOMETRIC DATA :

