


K11ST2040WF840NWW



## KOMBIC 100 SUT 2000 IP40 NW WFL WH/WH.

## Description:

Suspended track mounting downlight model KOMBIC 100 SUT by Lamp brand. Body made of white aluminum extrusion with reflector made of recycled polycarbonate R-PC FR WHITE TM non-brominated flame retardant additive. Flammability grade V0 according to UL94. White interior reflector. Heatsink made of die-cast aluminium. COB LED, colour temperature 4000K with CRI80. Luminaire with electronic wiring included. Insolation Class I. Lifetime: 50.000 L80 B10. With IP40 degree of protection. Group 0 photobiological safety. With Wide Flood optics to achieve a controlled light distribution and low UGR<19. Environmental Product Declaration - EPD®available, according to UNE-EN ISO 9001:2015 and UNE-EN ISO 14001:2015.

Finish: Matte white RAL 9010

Installation: Suspended

## TECHNICAL SPECIFICATIONS:

Light output:	1.343 lm	°K :	4000
Plum:	14,5W	CRI :	80
Efficacy:	92,6 lm/w	MacAdam:	3
UGR:	<19	Power Supply:	220-240V 50/60Hz
Type:	COB	Gear:	Electronic
LED Lifetime:	50.000 L80 B10 (Ta=25°C)		
Power:	12W		

Light output tolerance +/- 10%



## CUSTOM MADE OPTIONS:



KOMBIC 100 SUT

TECHNICAL DATA ON REVIEW

K11ST2040WF840NWW

KOMBIC 100 SUT 2000 IP40 NW WFL WH/WH.

PHOTOMETRIC DATA :

