# KOMBIC 100 SUT

**LAMP**
Worktitude for light

**K11ST2523RW830DBB**     –     **KOM 100 SUT 2500 IP23 WW RF WFL DA BK/BK**

**Description:**

**Finish:**     Matte black RAL 9011

**Weight:** 712   g

**Installation:**   Suspended

## TECHNICAL SPECIFICATIONS:

| | | | |
|---|---|---|---|
| **Light output:** | 1.908 lm | **ºK :** | 3000 |
| **Plum:** | 20W | **CRI :** | 80 |
| **Efficacy:** | 95,4 lm/w | **MacAdam:** | 3 |
| **Type:** | COB | **Power Supply:** | 220-240V 50/60Hz |
| **LED Lifetime:** | 50.000 L80 B10 (Ta=25ºC) | **Gear:** | Adjustable DALI |
| **Power:** | 19W | | |

*Light output tolerance +/- 10%*

EPD

13-03-2025

Pág.   1 / 2

**LAMP**
Worktitude for light

**K11ST2523RW830DBB**          **KOM 100 SUT 2500 IP23 WW RF WFL DA BK/BK**

## PHOTOMETRIC DATA :

K11ST2523RW830DBB

$\eta$ = 100%

Imax = 1293 cd/klm

UTE:

CIE:  99 100 100 100 100

180°

90°          90°

0°

alpha = 59,5º

100%

75%

BACK          FRONT

49,9 %          49,9 %

50%

25%

-8H   -4H   0H   4H   8H