K11ST2523RW840NBB   **-**   **KOMBIC 100 SUT 2500 IP23 NW RF WFL BK/BK**

Description:

Finish: Matte black RAL 9011

Weight: 502 g

Installation: Suspended

TECHNICAL SPECIFICATIONS:

Light output:	2.002 lm	**ºK :**	4000
Plum:	21,6W	**CRI :**	80
Efficacy:	92,8 lm/w	**MacAdam:**	3
Type:	COB	**Power Supply:**	220-240V 50/60Hz
LED Lifetime:	50.000 L80 B10 (Ta=25ºC)	**Gear:**	Electronic
Power:	19W		

Light output tolerance +/- 10%

EPD

LAMP
Worktitude for light

K11ST2523RW840NBB KOMBIC 100 SUT 2500 IP23 NW RF WFL BK/BK

PHOTOMETRIC DATA :

K11ST2523RW840NBB

η = 100%

Imax = 1293 cd/klm

UTE:

CIE: 99 100 100 100 100

alpha = 59,5º

BACK   FRONT

49,9 %   49,9 %

LAMP reserves the right to change the technical specifications of their products. These changes will allow the continual improvement of the products and will also ensure the conformity to current legal changes. Updated information is always available in our website www.lamp.es

13-03-2025

Pág. 2 / 2

Data according to regulations 2019/2020/EU and 2019/2015/EU