# KOMBIC 100 SUT TECHNICAL DATA ON REVIEW

# K11ST2540OP830DRB

# KOMBIC 100 SUT 2500 IP40 WW OP DA BR/BK.

#### **Description:**

Suspended track mounting downlight model KOMBIC 100 SUT by Lamp brand. Body made of black aluminum extrusion with reflector made of recycled polycarbonate R-PC FR WHITE TM non-brominated flame retardant additive. Flammability grade V0 according to UL94. Shiny metalized interior reflector and optical film. Heatsink made of die-cast aluminium. COB LED, colour temperature 3000K with CRI80. Luminaire with electronic wiring Dali included. Insolation Class I. Lifetime: 50.000 L80 B10. With IP40 degree of protection. Group 0 photobiological safety. Environmental Product Declaration - EPD®available, according to UNE-EN ISO 9001:2015 and UNE-EN ISO 14001:2015.

<b>∓</b> -	
1000	
¥	
180	
1	ø100mm

### Finish: BRILLIANT METALLIC POLYCARBONATE

Installation: Suspended

### **TECHNICAL SPECIFICATIONS:**

Light output:	1.959 lm	°K :	3000
Plum:	20,4W	CRI :	80
Efficacy:	96 lm/w	MacAdam:	3
Туре:	СОВ	Power Supply:	220-240V 50/60Hz
LED Lifetime:	50.000 L80 B10 (Ta=25°C)	Gear:	Adjustable DALI
Power:	17W		

### Light output tolerance +/- 10%



### **CUSTOM MADE OPTIONS:**



LAMP reserves the right to change the technical specifications of their products. These changes will allow the continual improvement of the products and will also ensure the conformity to current legal changes. Updated information is always available in our website www.lamp.es Worktitude for light