## **KOMBIC 100 SUT**


# **TECHNICAL DATA ON REVIEW**

## K11ST2540OP830DWW

## KOMBIC 100 SUT 2500 IP40 WW OP DA WH/WH.

### Description:

Suspended track mounting downlight model KOMBIC 100 SUT by Lamp brand. Body made of white aluminum extrusion with reflector made of recycled polycarbonate R-PC FR WHITE TM non-brominated flame retardant additive. Flammability grade V0 according to UL94. White interior reflector and optical film. Heatsink made of diecast aluminium. COB LED, colour temperature 3000K with CRI80. Luminaire with electronic wiring Dali included. Insolation Class I. Lifetime: 50.000 L80 B10. With IP40 degree of protection. Group 0 photobiological safety. Environmental Product Declaration - EPD®available, according to UNE-EN ISO 9001:2015 and UNE-EN ISO 14001:2015.



Finish: Matte white RAL 9010

Installation: Suspended

### **TECHNICAL SPECIFICATIONS:**

Light output: 1.951 lm °K: 3000 Plum: 20,4W CRI: 80 Efficacy: 95,6 lm/w 3 MacAdam:

Type: СОВ Power Supply: 220-240V 50/60Hz LED Lifetime: 50.000 L80 B10 (Ta=25°C) Gear: Adjustable DALI

Power: 17W

#### Light output tolerance +/- 10%

























## **CUSTOM MADE OPTIONS:**









Data according to regulations 2019/2020/EU and 2019/2015/EU









