KOMBIC 100 SUT

TECHNICAL DATA ON REVIEW


LAMP Worktitude for light

K11ST2540OP830NRW

KOMBIC 100 SUT 2500 IP40 WW OP BR/WH.

Description:

Suspended track mounting downlight model KOMBIC 100 SUT by Lamp brand. Body made of white aluminum extrusion with reflector made of recycled polycarbonate R-PC FR WHITE TM non-brominated flame retardant additive. Flammability grade V0 according to UL94. Shiny metalized interior reflector and optical film. Heatsink made of die-cast aluminium. COB LED, colour temperature 3000K with CRI80. Luminaire with electronic wiring included. Insolation Class I. Lifetime: 50.000 L80 B10. With IP40 degree of protection. Group 0 photobiological safety. Environmental Product Declaration - EPD®available, according to UNE-EN ISO 9001:2015 and UNE-EN ISO 14001:2015.



Finish: BRILLIANT METALLIC POLYCARBONATE

Installation: Suspended

TECHNICAL SPECIFICATIONS:

 Light output:
 1.959 lm
 °K:
 3000

 Plum:
 20,4W
 CRI:
 80

 Efficacy:
 96 lm/w
 MacAdam:
 3

Type: COB **Power Supply:** 220-240V 50/60Hz

LED Lifetime: 50.000 L80 B10 (Ta=25°C) Gear: Electronic

Power: 17W

Light output tolerance +/- 10%

























CUSTOM MADE OPTIONS:









Data according to regulations 2019/2020/EU and 2019/2015/EU









