


K11ST2540WF830DMW




## KOMBIC 100 SUT 2500 IP40 WW WFL DA MA/WH

**Description:**

Suspended track mounting downlight model KOMBIC 100 SUT by Lamp brand. Body made of white aluminum extrusion with reflector made of recycled polycarbonate R-PC FR WHITE TM non-brominated flame retardant additive. Flammability grade V0 according to UL94. Matte metallic interior reflector. Heatsink made of die-cast aluminium. COB LED, colour temperature 3000K with CRI80. Luminaire with electronic wiring Dali included. Insulation Class I. Lifetime: 50.000 L70 B10. With IP40 degree of protection. Group 0 photobiological safety. With Wide Flood optics to achieve a controlled light distribution and low glare level, less than UGR 17. Environmental Product Declaration - EPD@available, according to UNE-EN ISO 9001:2015 and UNE-EN ISO 14001:2015.

**Finish:** metalized polycarbonate mate**Installation:** Surface**TECHNICAL SPECIFICATIONS:**

<b>Light output:</b>	1.692 lm	<b>°K :</b>	3000
<b>Plum:</b>	21,6W	<b>CRI :</b>	80
<b>Efficacy:</b>	78,3 lm/w	<b>MacAdam:</b>	3
<b>UGR:</b>	<19	<b>Power Supply:</b>	220-240V 50/60Hz
<b>Type:</b>	COB	<b>Gear:</b>	Adjustable DALI
<b>LED Lifetime:</b>	50.000 L70 B10 (Ta=25°C)		
<b>Power:</b>	18W		

**Light output tolerance +/- 10%****CUSTOM MADE OPTIONS:**