KOMBIC 100 SUT


TECHNICAL DATA ON REVIEW

K11ST2540WF830NMW

KOMBIC 100 SUT 2500 IP40 WW WFL MA/WH.

Description:

Suspended track mounting downlight model KOMBIC 100 SUT by Lamp brand. Body made of white aluminum extrusion with reflector made of recycled polycarbonate R-PC FR WHITE TM non-brominated flame retardant additive. Flammability grade V0 according to UL94. Matte metallic interior reflector. Heatsink made of die-cast aluminium. COB LED, colour temperature 3000K with CRI80. Luminaire with electronic wiring included. Insolation Class I. Lifetime: 50.000 L70 B10. With IP40 degree of protection. Group 0 photobiological safety. With Wide Flood optics to achieve a controlled light distribution and low glare level, less than UGR 17. Environmental Product Declaration - EPD®available, according to UNE-EN ISO 9001:2015 and UNE-EN ISO 14001:2015.



Finish: metalized polycarbonate mate

Installation: Suspended

TECHNICAL SPECIFICATIONS:

Light output: 1.692 lm °K: 3000 Plum: 19,7W CRI: 80 Efficacy: 85,9 lm/w 3 MacAdam:

UGR: <19 Power Supply: 220-240V 50/60Hz Type: СОВ

LED Lifetime: 50.000 L70 B10 (Ta=25°C)

18W Power:

Light output tolerance +/- 10%

IP LED CLASE 40 3000°K





















CUSTOM MADE OPTIONS:



















Gear:

Electronic