# **KOMBIC 100 SURFACE TRACK**



K11TK1523RF940NMB

KOMBIC 100 TK 1500 IP23 9NW RF FL MA/BK

Description:

Finish: metalized polycarbonate mate

Weight: 502 g

Installation: 3-Circuit track

# **TECHNICAL SPECIFICATIONS:**

Light output: 1.474 lm °K: 4000 Plum: 14,1W CRI: 90 Efficacy: 100,4 lm/w R9: 65 UGR: <19 MacAdam: 3

Type: СОВ

LED Lifetime: 50.000 L80 B10 (Ta=25°C) Gear: Electronic

Power Supply:

220-240V 50/60Hz

Power: 13W

Light output tolerance +/- 10%

**EPD** 

Tel. +34937366800 Web www.lamp.es

# **KOMBIC 100 SURFACE TRACK**




K11TK1523RF940NMB


# KOMBIC 100 TK 1500 IP23 9NW RF FL MA/BK


## **PHOTOMETRIC DATA:**


$$\label{eq:continuity} \begin{split} \text{K11TK1523RF940NMB} \\ \eta &= 100\% \\ \text{Imax} &= 2200 \text{ cd/klm} \\ \text{UTE:} \end{split}$$


CIE: 98 99 100 100 100




















Data according to regulations 2019/2020/EU and 2019/2015/EU