Product datasheet

KOMBIC 100 SURFACE TRACK

LAMP
Worktitude for light

K11TK1523RW930DBB — **KOM 100 TK 1500 IP23 9WW RF WFL DA BK/BK**

Description:

Finish: Matte black RAL 9011

Weight: 712 g

Installation: 3-Circuit track

TECHNICAL SPECIFICATIONS:

Light output:	1.218 lm	**ºK :**	3000
Plum:	13,9W	**CRI :**	90
Efficacy:	87,6 lm/w	**R9 :**	53
UGR:	<19	**MacAdam:**	3
Type:	COB	**Power Supply:**	220-240V 50/60Hz
LED Lifetime:	50.000 L80 B10 (Ta=25ºC)	**Gear:**	Adjustable DALI
Power:	13W		

Light output tolerance +/- 10%

EPD

LAMP
Worktitude for light

K11TK1523RW930DBB   **KOM 100 TK 1500 IP23 9WW RF WFL DA BK/BK**

PHOTOMETRIC DATA :

K11TK1523RW930DBB

η = 100%

Imax = 1293 cd/klm

UTE:

CIE: 99 100 100 100 100

alpha = 59,5º

BACK   FRONT

49,9 %   49,9 %

Melanopic Lux Ratio: 0.550

Rf

1 - Limits on the Planckian locus

Rg

2 - Limits for practical sources

Rf 90.1 – Rg 100.3

LAMP reserves the right to change the technical specifications of their products. These changes will allow the continual improvement of the products and will also ensure the conformity to current legal changes. Updated information is always available in our website www.lamp.es

13-03-2025

Pág.   2 / 2

Data according to regulations 2019/2020/EU and 2019/2015/EU