


## KOMBIC 100 SURFACE TRACK

K11TK1540OP930NWW



## KOMBIC 100 TK 1500 IP40 9WW OP WH/WH.

**Description:**

Downlight to adapt to three-phase track model KOMBIC 100 TK by Lamp brand. Body made of white aluminum extrusion with reflector made of recycled polycarbonate R-PC FR WHITE TM non-brominated flame retardant additive. Flammability grade V0 according to UL94. White interior reflector and optical film. Heatsink made of die-cast aluminium. COB LED, colour temperature 3000K with CRI90. Luminaire with electronic wiring included. Insolation Class I. Lifetime: 50.000 L80 B10. With IP40 degree of protection. Group 0 photobiological safety. Environmental Product Declaration - EPD@available, according to UNE-EN ISO 9001:2015 and UNE-EN ISO 14001:2015.

**Finish:** Matte white RAL 9010**Weight:** 502 g**Installation:** 3-Circuit track**TECHNICAL SPECIFICATIONS:**

<b>Plum:</b>	13,7W	<b>°K :</b>	3000
<b>Type:</b>	COB	<b>CRI :</b>	90
<b>LED Lifetime:</b>	50.000 L80 B10 (Ta=25°C)	<b>R9 :</b>	68
<b>Power:</b>	12W	<b>MacAdam:</b>	3
		<b>Power Supply:</b>	220-240V 50/60Hz
		<b>Gear:</b>	Electronic

**CUSTOM MADE OPTIONS:**