


KOMBIC 100 SURFACE TRACK

K11TK1540WF927DMB

- KOMBIC 100 TK 1500 IP40 9VWW WFL DA MA/B

**Description:**

Downlight to adapt to three-phase track model KOMBIC 100 TK by Lamp brand. Body made of black aluminum extrusion with reflector made of recycled polycarbonate R-PC FR WHITE TM non-brominated flame retardant additive. Flammability grade V0 according to UL94. Matte metallic interior reflector. Heatsink made of die-cast aluminium. COB LED, colour temperature 2700K with CRI90. Luminaire with electronic wiring DALI included. Insulation Class I. Lifetime: >100.000 L90 B10. With IP40 degree of protection. Group 0 photobiological safety. With Wide Flood optics to achieve a controlled light distribution and low glare level, less than UGR<19. Environmental Product Declaration - EPD@available, according to UNE-EN ISO 9001:2015 and UNE-EN ISO 14001:2015.

Finish: metalized polycarbonate mate

Installation: 3-Circuit track
TECHNICAL SPECIFICATIONS:

Light output:	1.034 lm	°K :	2700
Plum:	10W	CRI :	90
Efficacy:	103,4 lm/w	R9 :	57
UGR:	<19		
LED Lifetime:	>100.000h L90 B10 (Ta=25°C)		
Power:	8,5W		

Light output tolerance +/- 10%
**CUSTOM MADE OPTIONS:**

KOMBIC 100 SURFACE TRACK



K11TK1540WF927DMB

KOMBIC 100 TK 1500 IP40 9VWW WFL DA MA/B

PHOTOMETRIC DATA :

