

## KOMBIC 100 SURFACE TRACK


K11TK2040OP9TWDRW



## KOMBIC 100 TK 2000 IP40 TW OP DA BR/WH.

**Description:**

Downlight to adapt to three-phase track model KOMBIC 100 TK by Lamp brand. Body made of white aluminum extrusion with reflector made of recycled polycarbonate R-PC FR WHITE TM non-brominated flame retardant additive. Flammability grade V0 according to UL94. Shiny metallic interior reflector and optical film. Heatsink made of die-cast aluminium. COB LED, with dynamic white colour temperature (2700-6500K) with CRI 90. Luminaire with electronic wiring Dali DT8 included. Insolation Class I. Lifetime: 70.000 L80 B10. With IP40 degree of protection. Group 0 photobiological safety. Environmental Product Declaration - EPD®available, according to UNE-EN ISO 9001:2015 and UNE-EN ISO 14001:2015.

**Finish:** BRILLIANT METALLIC POLYCARBONATE

**Installation:** 3-Circuit track
**TECHNICAL SPECIFICATIONS:**

<b>Light output:</b>	1.349 lm	<b>°K :</b>	2700-6500
<b>Plum:</b>	20,7W	<b>CRI :</b>	90
<b>Efficacy:</b>	69,2 lm/w	<b>MacAdam:</b>	3
<b>Type:</b>	COB	<b>Power Supply:</b>	220-240V 50/60Hz
<b>LED Lifetime:</b>	70.000 L80 B10 (Ta=25°C)	<b>Gear:</b>	Adjustable DALI
<b>Power:</b>	16W		

*Light output tolerance +/- 10%*
**CUSTOM MADE OPTIONS:**