


## KOMBIC 100 SURFACE TRACK

K11TK2040WF830NMB



## KOMBIC 100 TK 2000 IP40 WW WFL MA/BK.

**Description:**

Downlight to adapt to three-phase track model KOMBIC 100 TK by Lamp brand. Body made of black aluminum extrusion with reflector made of recycled polycarbonate R-PC FR WHITE TM non-brominated flame retardant additive. Flammability grade V0 according to UL94. Matte metallic interior. Heatsink made of die-cast aluminium. COB LED, colour temperature 3000K with CRI80. Luminaire with electronic wiring included. Insolation Class I. Lifetime: 50.000 L80 B10. With IP40 degree of protection. Group 0 photobiological safety. With Wide Flood optics to achieve a controlled light distribution and low glare level, less than UGR 17. Environmental Product Declaration - EPD@available, according to UNE-EN ISO 9001:2015 and UNE-EN ISO 14001:2015.

**Finish:** metalized polycarbonate mate

**Installation:** 3-Circuit track
**TECHNICAL SPECIFICATIONS:**

<b>Light output:</b>	1.268 lm	<b>°K :</b>	3000
<b>Plum:</b>	14,5W	<b>CRI :</b>	80
<b>Efficacy:</b>	87,4 lm/w	<b>MacAdam:</b>	3
<b>UGR:</b>	<19	<b>Power Supply:</b>	220-240V 50/60Hz
<b>Type:</b>	COB	<b>Gear:</b>	Electronic
<b>LED Lifetime:</b>	50.000 L80 B10 (Ta=25°C)		
<b>Power:</b>	12W		

*Light output tolerance +/- 10%*
**CUSTOM MADE OPTIONS:**