


KOMBIC 100 SURFACE TRACK

K11TK2040WF930NBW



KOMBIC 100 TK 2000 IP40 9WW WFL BK/WH.

Description:

Downlight to adapt to three-phase track model KOMBIC 100 TK by Lamp brand. Body made of white aluminum extrusion with reflector made of recycled polycarbonate R-PC FR WHITE TM non-brominated flame retardant additive. Flammability grade V0 according to UL94. Black interior reflector. Heatsink made of die-cast aluminium. COB LED, colour temperature 3000K with CRI90. Luminaire with electronic wiring included. Insolation Class I. Lifetime: 50.000 L70 B10. With IP40 degree of protection. Group 0 photobiological safety. With Wide Flood optics to achieve a controlled light distribution and low glare level, less than UGR 17. Environmental Product Declaration - EPD@available, according to UNE-EN ISO 9001:2015 and UNE-EN ISO 14001:2015.

Finish: Matte black RAL 9011**Weight:** 502 g**Installation:** 3-Circuit track**TECHNICAL SPECIFICATIONS:**

Light output:	1.472 lm	°K :	3000
Plum:	20,3W	CRI :	90
Efficacy:	72,5 lm/w	R9 :	60
UGR:	<19	MacAdam:	3
Type:	COB	Power Supply:	220-240V 50/60Hz
LED Lifetime:	50.000 L80 B10 (Ta=25°C)	Gear:	Electronic
Power:	17W		

Light output tolerance +/- 10%**CUSTOM MADE OPTIONS:**

KOMBIC 100 SURFACE TRACK



K11TK2040WF930NBW

KOMBIC 100 TK 2000 IP40 9WW WFL BK/WH.

PHOTOMETRIC DATA :

