


KOMBIC 100 SURFACE TRACK

K11TK25400P840NWB



KOMBIC 100 TK 2500 IP40 NW OP WH/BK.

Description:

Downlight to adapt to three-phase track model KOMBIC 100 TK by Lamp brand. Body made of black aluminum extrusion with reflector made of recycled polycarbonate R-PC FR WHITE TM non-brominated flame retardant additive. Flammability grade V0 according to UL94. White interior reflector and optical film. Heatsink made of die-cast aluminium. COB LED, colour temperature 4000K with CRI80. Luminaire with electronic wiring included. Insolation Class I. Lifetime: 50.000 L80 B10. With IP40 degree of protection. Group 0 photobiological safety. Environmental Product Declaration - EPD@available, according to UNE-EN ISO 9001:2015 and UNE-EN ISO 14001:2015.

Finish: Matte white RAL 9010**Installation:** 3-Circuit track**TECHNICAL SPECIFICATIONS:**

Light output:	2.067 lm	°K :	4000
Plum:	18,6W	CRI :	80
Efficacy:	111,1 lm/w	MacAdam:	3
Type:	COB	Power Supply:	220-240V 50/60Hz
LED Lifetime:	50.000 L80 B10 (Ta=25°C)	Gear:	Electronic
Power:	17W		

Light output tolerance +/- 10%**CUSTOM MADE OPTIONS:**