KOMBIC 150 DOWNLIGHT

Worktitude for light

K21RD2023RF830DBW



KOMBIC 150 RD 2100 IP23 WW RF FL DA BK/W

Description:

Round recessed downlight model KOMBIC 150 RD by Lamp brand. Reflector made of recycled polycarbonate R-PC FR WHITE TM non-brominated flame retardant additive. Flammability grade V0 according to UL94. Black interior reflector and frame in white finish. Heatsink made of die-cast aluminium. COB LED, colour temperature 3000K with CRI80. Luminaire with electronic wiring Dali included. Insolation Class II. Lifetime: 66.000 L90 B10. With IP23 degree of protection. Group 0 photobiological safety. Reflector aluminium Flood to achieve a controlled light distribution and low UGR<19.

Finish: Matte black RAL 9011

Weight: 704 g

Installation: Recessed



TECHNICAL SPECIFICATIONS:

 Light output:
 1.835 lm
 °K:
 3000

 Plum:
 13,9W
 CRI:
 80

 Efficacy:
 132 lm/w
 MacAdam:
 3

 UGR:
 <19</th>
 Power Supply:
 220-240V 50/60Hz

 Type:
 COB
 Gear:
 Adjustable DALI

LED Lifetime: 66.000 L90 B10 (Ta=25°C)

Power: 12W

Light output tolerance +/- 10%























CUSTOM MADE OPTIONS:









Data according to regulations 2019/2020/EU and 2019/2015/EU













KOMBIC 150 DOWNLIGHT



K21RD2023RF830DBW

KOMBIC 150 RD 2100 IP23 WW RF FL DA BK/W

PHOTOMETRIC DATA:

K21RD2023RF830DBW η = 100% Imax = 2122 cd/klm UTE: CIE: 100 100 100 100 100





