**Product datasheet**

# KOMBIC 150 DOWNLIGHT

**K21RD2023RF840DBB**



## KOMBIC 150 RD 2100 IP23 NW RF FL DA BK/B

### Description:

Round recessed downlight model KOMBIC 150 RD by Lamp brand. Reflector made of recycled polycarbonate R-PC FR WHITE TM non-brominated flame retardant additive. Flammability grade V0 according to UL94. Interior reflector and frame in black finish. Heatsink made of die-cast aluminium. COB LED, colour temperature 4000K with CRI80. Luminaire with electronic wiring Dali included. Insolation Class II. Lifetime: 66.000 L90 B10. With IP23 degree of protection. Group 0 photobiological safety. Reflector aluminium Flood to achieve a controlled light distribution and low UGR<19.




**Finish:** Matte black RAL 9011

**Weight:** 704 g

**Installation:** Recessed

### TECHNICAL SPECIFICATIONS:

| | | | |
|---|---|---|---|
| **Light output:** | 1.927 lm | **ºK :** | 4000 |
| **Plum:** | 13,9W | **CRI :** | 80 |
| **Efficacy:** | 138,6 lm/w | **MacAdam:** | 3 |
| **UGR:** | <19 | **Power Supply:** | 220-240V 50/60Hz |
| **Type:** | COB | **Gear:** | Adjustable DALI |
| **LED Lifetime:** | 66.000 L90 B10 (Ta=25ºC) | | |
| **Power:** | 12W | | |

***Light output tolerance +/- 10%***




### CUSTOM MADE OPTIONS:

# KOMBIC 150 DOWNLIGHT

**K21RD2023RF840DBB** **KOMBIC 150 RD 2100 IP23 NW RF FL DA BK/B**

**PHOTOMETRIC DATA :**

K21RD2023RF840DBB

η = 100%

Imax = 2122 cd/klm

UTE:

CIE: 100 100 100 100 100














LAMP reserves the right to change the technical specifications of their products. These changes will allow the continual improvement of the products and will also ensure the conformity to current legal changes. Updated information is always available in our website www.lamp.es

Data according to regulations 2019/2020/EU and 2019/2015/EU