

# KOMBIC 150 DOWNLIGHT

K21RD2023RF840NWW




**KOMBIC 150 RD 2100 IP23 NW RF FL WH/WH**

**Description:**

Round recessed downlight model KOMBIC 150 RD by Lamp brand. Reflector made of recycled polycarbonate R-PC FR WHITE TM non-brominated flame retardant additive. Flammability grade V0 according to UL94. Interior reflector and frame in white finish. Heatsink made of die-cast aluminium. COB LED, colour temperature 4000K with CRI80. Luminaire with electronic wiring included. Insolation Class II. Lifetime: 66.000 L90 B10. With IP23 degree of protection. Group 0 photobiological safety. Reflector aluminium Flood to achieve a controlled light distribution and low UGR<19.

**Finish:** Matte white RAL 9010

**Weight:** 704 g




**Installation:** Recessed

**TECHNICAL SPECIFICATIONS:**

<b>Light output:</b>	1.881 lm	<b>°K :</b>	4000
<b>Plum:</b>	13,9W	<b>CRI :</b>	80
<b>Efficacy:</b>	135,3 lm/w	<b>MacAdam:</b>	3
<b>UGR:</b>	<19	<b>Power Supply:</b>	220-240V 50/60Hz
<b>Type:</b>	COB	<b>Gear:</b>	Electronic
<b>LED Lifetime:</b>	66.000 L90 B10 (Ta=25°C)		
<b>Power:</b>	12W		

*Light output tolerance +/- 10%*



**CUSTOM MADE OPTIONS:**



# KOMBIC 150 DOWNLIGHT

K21RD2023RF840NWW

KOMBIC 150 RD 2100 IP23 NW RF FL WH/WH

## PHOTOMETRIC DATA :

