## **KOMBIC 150 DOWNLIGHT**


## K21RD2023RF927NWW



## KOMBIC 150 RD 2400 IP23 9VWW RF FL WH/WH

## Description:

Round recessed downlight model KOMBIC 150 RD by Lamp brand. Reflector made of recycled polycarbonate R-PC FR WHITE TM non-brominated flame retardant additive. Flammability grade V0 according to UL94. Interior reflector and frame in white finish. Heatsink made of die-cast aluminium. COB LED, colour temperature 2700K with CRI90. Luminaire with electronic wiring included. Insolation Class II. Lifetime: 66.000 L90 B10. With IP23 degree of protection. Group 0 photobiological safety. Reflector aluminium Flood to achieve a controlled light distribution and low UGR<19.



Finish: Matte white RAL 9010

Weight: 704 g

Installation: Recessed

## **TECHNICAL SPECIFICATIONS:**

Light output: 1.945 lm °K: 2700 Plum: 19,1W CRI: 90 Efficacy: 101,8 lm/w R9: 53 UGR: <19 MacAdam: 3

Type: СОВ Power Supply: 220-240V 50/60Hz

LED Lifetime: 66.000 L90 B10 (Ta=25°C) Gear: Electronic

17W Power:

# Light output tolerance +/- 10%



























# **CUSTOM MADE OPTIONS:**









Data according to regulations 2019/2020/EU and 2019/2015/EU













# **KOMBIC 150 DOWNLIGHT**



**K21RD2023RF927NWW** 

# **KOMBIC 150 RD 2400 IP23 9VWW RF FL WH/WH**

# **PHOTOMETRIC DATA:**

K21RD2023RF927NWW  $\eta$  = 100% lmax = 2155 cd/klmUTE:

CIE: 99 100 100 100 100



