
# **KOMBIC 150 DOWNLIGHT**

#### K21RD2023RF930DWW





#### KOMBIC 150 RD 2400 IP23 9WW RF FL DA W/W

#### **Description:**

Round recessed downlight model KOMBIC 150 RD by Lamp brand. Reflector made of recycled polycarbonate R-PC FR WHITE TM non-brominated flame retardant additive. Flammability grade V0 according to UL94. Interior reflector and frame in white finish. Heatsink made of die-cast aluminium. COB LED, colour temperature 3000K with CRI90. Luminaire with electronic wiring Dali included. Insolation Class II. Lifetime: 66.000 L80 B10. With IP23 degree of protection. Group 0 photobiological safety. Reflector aluminium Flood to achieve a controlled light distribution and low UGR<19.

Finish: Matte white RAL 9010

Weight: 704 g

Installation: Recessed

#### **TECHNICAL SPECIFICATIONS:**

Light output:	2.039 lm	<b>°K</b> :	3000
Plum:	19,1W	CRI :	90
Efficacy:	106,8 lm/w	R9 :	54
UGR:	<19	MacAdam:	3
Туре:	СОВ	Power Supply:	220-240V 50/60Hz
LED Lifetime:	66.000 L90 B10 (Ta=25⁰C)	Gear:	Adjustable DALI
Power:	17W		

### Light output tolerance +/- 10%



### **CUSTOM MADE OPTIONS:**



Worktitude for light

## **KOMBIC 150 DOWNLIGHT**

K21RD2023RF930DWW

KOMBIC 150 RD 2400 IP23 9WW RF FL DA W/W



### **PHOTOMETRIC DATA :**

